

MHD flow of visco-elastic [Oldroyd (1958) model] liquid of first order through porous media between two parallel flat plates

RAVINDRA KUMAR¹, K.K. SINGH and A.K. SHARMA²

¹Department of Mathematics, Agra College, Agra U.P. (INDIA)

²Department of Mathematics, K.K.P.G.College Etawah U.P. (INDIA)

Email ID: rupal.maths@gmail.com ; kk.singh@bsacet.org

Email ID: aksharma.maths@gmail.com

(Acceptance Date 15th May, 2012)

Abstract

Present paper is concerned with the oscillatory motion of conducting visco-elastic [Oldroyd (1958) model] liquid of first order through porous medium between two infinite flat plates both of which execute simple harmonic motion in the plane of plates with different amplitudes and frequencies under the influence of an uniform magnetic field applied perpendicular to the flat plates. Some particular cases have also been discussed in detail.

Introduction

The study of the physics of flow through porous medium has become the basis of many scientific and engineering applications. This type of flow is of great importance in the petroleum engineering concerned with the movement of oil, gas and water through the reservoir of an oil or gas field to the hydrologist in the study of the migration of underground water and to the chemical engineer in the filtration process.

The visco-elastic fluids are particular

cases of non-Newtonian fluids which exhibit appreciable elastic behaviour and stress-strain velocity relations and are time dependent. The subject of Rheology is of great technological importance as in many branches of industry, the problem arises of designing apparatus to transport or to process substances which can not be governed by the classical stress-strain velocity relations. Examples of such substances and the process are many, the extrusion of plastics, in the manufacture of rayon, nylon or other textiles, fibres, visco-elastic effects are encountered when the spinning solutions are transported or forced through spinnerets and in the manufacture of lubricating greases and

¹616, Pal Colony, Near Shesh Cold Store, Ashok Nagar, Etawah (U.P.)-206001

rubbers.

The magneto hydrodynamic¹ flow means, the motion of the electrically conducting fluid in the presence of Maxwell electro-magnetic field. The Flow of the conducting fluid is effectively changed by the presence of the magnetic field and the magnetic field is also perturbed due to the motion of the conducting fluid. This phenomena is therefore interlocking in character and the discipline of this branch of science is called Magnetohydrodynamics (MHD). It is equally rich and admits wider applications in Engineering, Technology, Cosmology, Astrophysics and other applied sciences. It has tremendously developed in recent years and some of the monographs in this direction are due to Ferraro-Plumpton³, Pai¹⁰, Shercliff¹⁶, Sutton and Shermann¹⁹, Jefferey⁶ and Cowling². Many research workers have paid their attention towards the application of visco-elastic fluid flow of different category through porous medium in channels of various cross-sections such as

Gupta and Sharma⁴; Singh, Shankar and Singh¹⁸; Singh and Kumar¹⁷; Kundu and Sengupta⁹; Hassanien⁵; Sengupta and Basak¹⁴; Pundhir and Pundhir¹¹; Rehman and Alam Sarkar¹²; Saroa¹³; Sharma and Pareek (2006); Kumar, Singh and Sharma⁸ etc.

The aim of the present paper is to study the oscillatory motion of visco-elastic Oldroyd liquid of first order through porous medium between two infinite parallel flat plates under the influence of uniform magnetic field applied perpendicular to the flat plates. Both the plates are assumed to be oscillating harmonically with different amplitudes and frequencies. Some particular cases have also been discussed in detail.

Governing Equations of Motion:

The rheological equations for visco-elastic [Oldroyd (1958) model] liquid are:

$$\begin{aligned} P_{ik} &= -p\delta_{ik} + P'_{ik} \\ p'_{ik} + \lambda_1 \frac{D}{Dt} p'_{ik} + \mu_0 p'_{jj} e_{ik} - \mu_1 (p'_{ij} e_{jk} + p'_{jk} e_{ij}) - \nu_1 p'_{jl} e_{jl} \delta_{ik} \\ &= 2\eta_0 \left(e_{ik} + \lambda_2 \frac{D}{Dt} e_{ik} - 2\mu_2 e_{ij} e_{jk} + \nu_2 e_{jl} \delta_{ik} \right) \end{aligned}$$

with the equation of incompressibility

$$e_{ii} = 0$$

where

$$\frac{D}{Dt} b_{ik} = \frac{\partial}{\partial t} b_{ik} + v_{ij} b_{ik'j} + w_{ij} b_{jk} + w_{kj} b_{ij}$$

$$e_{ij} = \frac{1}{2} (v_{ki} + v_{ik})$$

$$w_{ik} = \frac{1}{2} (v_{ki} - v_{ik})$$

e_{ik} = rate of strain tensor

p_{ik} = stress tensor

λ_1 = relaxation time

λ_2 = retardation time

η_0 = coefficient of viscosity

and $\mu_0, \mu_1, \mu_2, \nu_1$ and ν_2 are the material constants, each being of the dimension of time.

For $\eta_0 > 0, \lambda_1 = \mu_1 = \mu_2 = \lambda_2 = 0, \mu_0$

$= \nu_1 = \nu_2 = 0$ the liquid will behave as ordinary viscous liquid.

Formulation of the Problem:

Let d be the distance between parallel plates, x -axis along the lower plate in the direction of flow of liquid and y -axis perpendicular to the plates. Supposing that the lower and upper plates execute oscillations with different amplitudes v_1, v_2 and frequencies ω_1, ω_2 respectively.

Following Ghosh (1968) the equation of motion for visco-elastic Oldroyd liquid of first order through porous medium between oscillating plates is given by

$$\left(1 + \lambda_1 \frac{\partial}{\partial t}\right) \frac{\partial u}{\partial t} = -\frac{1}{\rho} \left(1 + \lambda_1 \frac{\partial}{\partial t}\right) \frac{\partial p}{\partial x}$$

$$\begin{aligned} y^* &= \frac{1}{d} y, & t^* &= \frac{\nu}{d^2} t, & u^* &= \frac{d}{\nu} u, & \lambda_1^* &= \frac{\nu}{d^2} \lambda_1, & \lambda_2^* &= \frac{\nu}{d^2} \lambda_2, \\ v_1^* &= \frac{d}{\nu} v_1, & v_2^* &= \frac{d}{\nu} v_2, & \omega_1^* &= \frac{d^2}{\nu} \omega_1, & \omega_2^* &= \frac{d^2}{\nu} \omega_2, & K^* &= \frac{1}{d^2} K \end{aligned}$$

$$+ \nu \left(1 + \lambda_2 \frac{\partial}{\partial t}\right) \frac{\partial^2 u}{\partial y^2} - \left(\frac{\sigma B_0^2}{\rho} + \frac{\nu}{K}\right) \left(1 + \lambda_1 \frac{\partial}{\partial t}\right) u \quad (1)$$

where $\nu = \frac{\mu}{\rho}$ = kinetic viscosity, μ the

coefficient of viscosity, u the velocity of liquid in the direction of oscillation, p the fluid pressure, t the time, K the permeability of porous medium and B_0 is the magnetic inductivity.

Assuming the pressure gradient to be zero, the equation (1) becomes

$$\begin{aligned} \left(1 + \lambda_1 \frac{\partial}{\partial t}\right) \frac{\partial u}{\partial t} &= \nu \left(1 + \lambda_2 \frac{\partial}{\partial t}\right) \frac{\partial^2 u}{\partial y^2} \\ &- \left(\frac{\sigma B_0^2}{\rho} + \frac{\mu}{K}\right) \left(1 + \lambda_1 \frac{\partial}{\partial t}\right) u \end{aligned} \quad (2)$$

The boundary conditions are:

$$\left. \begin{aligned} u &= v_1 e^{-i\omega_1 t} & \text{when } y &= 0 \\ u &= v_2 e^{-i\omega_2 t} & \text{when } y &= d \end{aligned} \right\} \quad (3)$$

Introducing the following non-dimensional quantities:

in (2) and (3) and then dropping stars, we get or

$$\left(1 + \lambda_1 \frac{\partial}{\partial t}\right) \frac{\partial u}{\partial t} = \frac{\partial^2 u}{\partial y^2} - \left(M^2 + \frac{1}{K}\right) \left(1 + \lambda_1 \frac{\partial}{\partial t}\right) u \quad (4)$$

and

$$\left. \begin{aligned} u &= v_1 e^{-i\omega_1 t} & \text{when } y &= 0 \\ u &= v_2 e^{-i\omega_2 t} & \text{when } y &= 1 \end{aligned} \right\} \quad (5)$$

where $M = dB_0 \sqrt{\frac{\sigma}{\mu}}$ (Hartmann Number).

Solution of the Problem:

We look for a solution of equation (4) in the form

$$u = v_1 f(y) e^{-i\omega_1 t} + v_2 g(y) e^{-i\omega_2 t} \quad (6)$$

which is evidently periodic in t .

Substituting (6) in (4), we get

$$\begin{aligned} v_1 e^{-i\omega_1 t} & \left[(1 - i\omega_1 \lambda_2) \frac{d^2 f}{dy^2} + \left\{ \lambda_1 \omega_1^2 + i\omega_1 \right. \right. \\ & \left. \left. - \left(M^2 + \frac{1}{K} \right) (1 - i\omega_1 \lambda_1) \right\} f \right] \\ & + v_2 e^{-i\omega_2 t} \left[(1 - i\omega_2 \lambda_2) \frac{d^2 g}{dy^2} + \left\{ \lambda_1 \omega_2^2 + i\omega_2 \right. \right. \\ & \left. \left. - \left(M^2 + \frac{1}{K} \right) (1 - i\omega_2 \lambda_1) \right\} g \right] = 0 \quad (7) \end{aligned}$$

By assumption v_1 and v_2 are not zero, we have

$$\frac{d^2 f}{dy^2} + \frac{i\omega_1 (1 - i\omega_1 \lambda_1) - \left(M^2 + \frac{1}{K} \right) (1 - i\omega_1 \lambda_1)}{(1 - i\omega_1 \lambda_2)} f = 0$$

$$\frac{d^2 f}{dy^2} + \frac{(1 - i\omega_1 \lambda_1) \left\{ i\omega_1 - \left(M^2 + \frac{1}{K} \right) \right\}}{(1 - i\omega_1 \lambda_2)} f = 0$$

or

$$\frac{d^2 f}{dy^2} + m^2 f = 0 \quad (8)$$

and

$$\frac{d^2 g}{dy^2} + \frac{i\omega_2 (1 - i\omega_2 \lambda_1) - \left(M^2 + \frac{1}{K} \right) (1 - i\omega_2 \lambda_1)}{(1 - i\omega_2 \lambda_2)} g = 0$$

or

$$\frac{d^2 g}{dy^2} + \frac{(1 - i\omega_2 \lambda_1) \left\{ i\omega_2 - \left(M^2 + \frac{1}{K} \right) \right\}}{(1 - i\omega_2 \lambda_2)} g = 0$$

or

$$\frac{d^2 g}{dy^2} + n^2 g = 0 \quad (9)$$

where

$$m^2 = \frac{(1 - i\omega_1 \lambda_1) \left\{ i\omega_1 - \left(M^2 + \frac{1}{K} \right) \right\}}{(1 - i\omega_1 \lambda_2)} \text{ and}$$

$$n^2 = \frac{(1 - i\omega_2 \lambda_1) \left\{ i\omega_2 - \left(M^2 + \frac{1}{K} \right) \right\}}{(1 - i\omega_2 \lambda_2)}$$

The solution of equation (8) is

$$f(y) = A \cos my + B \sin my \quad (10)$$

and corresponding boundary conditions for

$f(y)$ are

$$\left. \begin{array}{ll} f(y) = 1 & \text{when } y = 0 \\ f(y) = 0 & \text{when } y = 1 \end{array} \right\} \quad (11)$$

$\therefore$ From (10) and (11), we get

$$f(y) = \cos m y - \frac{\cos m}{\sin m} \sin m y \quad (12)$$

Similarly from (9) with boundary conditions $g(0) = 0$ and $g(1) = 1$, we get

$$g(y) = \frac{\sin n y}{\sin n} \quad (13)$$

Now putting the values of $f(y)$ and $g(y)$ in (6), we get the velocity of visco-elastic Oldroyd (1958) type liquid through porous medium between two parallel flat plates under the influence of uniform magnetic field.

$$u = v_1 \frac{\sin m (1-y)}{\sin m} e^{-i\omega_1 t} + v_2 \frac{\sin n y}{\sin n} e^{-i\omega_2 t} \quad (14)$$

Particular Cases:

Case I: If both the plates oscillate with same amplitudes and different frequencies then $v_1 = v_2 = v$ (say) and from (14)

$$u = v \left\{ \frac{\sin m (1-y)}{\sin m} e^{-i\omega_1 t} + \frac{\sin n y}{\sin n} e^{-i\omega_2 t} \right\} \quad (15)$$

Case II: If both the plates oscillate with same frequencies and different amplitudes then $\omega_1 = \omega_2 = \omega$ (say) and from (14)

$$u = \left\{ v_1 \frac{\sin m (1-y)}{\sin m} + v_2 \frac{\sin n y}{\sin n} \right\} e^{-i\omega t} \quad (16)$$

$$\text{where } m^2 = \frac{(1-i\omega\lambda_1) \left\{ i\omega - \left(M^2 + \frac{1}{K} \right) \right\}}{(1-i\omega\lambda_2)} = n^2$$

Case III: If both the plates oscillate with same amplitudes and frequencies then $v_1 = v_2 = v$ (say) and $\omega_1 = \omega_2 = \omega$ (say) and from (14)

$$u = v \left\{ (1 - \cot m) \sin m y + \cos m y \right\} e^{-i\omega t} \quad (17)$$

$$\text{where } m^2 = \frac{(1-i\omega\lambda_1) \left\{ i\omega - \left(M^2 + \frac{1}{K} \right) \right\}}{(1-i\omega\lambda_2)}$$

Case IV (a): If porous medium is withdrawn then $K = \infty$ and from (14)

$$u = v_1 \frac{\sin m (1-y)}{\sin m} e^{-i\omega_1 t} + v_2 \frac{\sin n y}{\sin n} e^{-i\omega_2 t} \quad (18)$$

$$\text{where } m^2 = \frac{i\omega_1 (1-i\omega_1\lambda_1)}{(1-i\omega_1\lambda_2)} \text{ and}$$

$$n^2 = \frac{i\omega_2 (1-i\omega_2\lambda_1)}{(1-i\omega_2\lambda_2)}.$$

All the results agree with Kumar, Singh and Sharma (2011).

(b): If Magnetic field is withdrawn i.e. $M \rightarrow 0$ then all the expressions agree with Kumar, Mishra and Singh^{7,8}.

(c): If both $M \rightarrow 0$ and $K \rightarrow \infty$, we get all expressions of velocity of fluids in absence of magnetic field and porous medium.

References

1. Agarwal, M. and Agarwal, N., *Proc. Nat. Acad. Sci. India*, Vol.76 (A), No.1, p-55 (2006).
2. Cowling, T. G., *Magnetohydrodynamics*, Bristol England Adam Hilger Limited (1976).
3. Ferraro, V.C.A. and Plumpton, C., *An Introduction to Magnetohydrodynamics*, Oxford Univ. Press (1961).
4. Gupta, M. and Sharma, S., *Acta Ciencia Indica*, Vol. XVI (M), No.4, p-437 (1990).
5. Hassanien, I.A., *ZAMM*, Vol.82, No.6, p-409 (2002).
6. Jefferey, A., *Magnetohydrodynamics*, Oliver and Boyd (1965).
7. Kumar, R., Mishra, G. and Singh, K. K., *Int. Jour. Math. Arch.* Vol. 2, No.4 Apr., p-584 (2011).
8. Kumar, R., Singh, K.K. and Sharma, A.K., *Jour. Purvanchal Acad. Sci.*, Vol.15, p-80 (2009).
Ultra Scientist Vol.22, No.1, p-169 (2010).
Int. Jour. Math. Arch. Vol. 2, No. 4 Apr., p-579 (2011).
9. Kundu, S.K. and Sengupta, P.R., *Proc. Nat. Acad. Sci.*, Vol. 23, No.2, p-291 (2001).
10. Pai, S. I., *Magnetohydrodynamics and Plasmadynamics*, Prantice Hall London (1962).
11. Pundhir, S.K. and Pundhir, R., *Acta Ciencia Indica*, Vol. XXIX M, No.3, p-487 (2003).
12. Rehman, M. M. and Alam Sarkar, M. S., *Bull. Cal. Math. Soc.*, Vol.96, No.6, p-463 (2004).
13. Saroa, M.S., *Proc. Ind. Nat. Sci. Acad.*, Vol. 72, No.3, p-121 (2006).
14. Sengupta, P. R. and Basak, P., *Ind. Jour. Theo. Phy.*, Vol.50, No.3, p-203 (2002).
15. Sharma, P.R. and Pareek, D., *Bull. Pure Appl. Sci.*, Vol. 20, No. 1, p-103 (2001).
16. Shercliff, J.A., *A text book of magnetohydrodynamics*, Pergamon Press (1965).
17. Singh, K.K. and Kumar, R., *Acta Ciencia Indica*, Vol. XXIV M, No.4, p-321 (1998).
18. Singh, K. K., Shankar, U. and Singh, C., *Pure Appl. Sci.*, Vol. XII, No. 1-2, p-95 (1995).
19. Sutton, G. W. and Shermann, A., *Engg. Magnetohydrodynamics*, McGraw Hill Book Company (1965).